

## CW Single Mode Laser / CW-SM-Q-2209-15-1-HHL-L

CW Single Mode Lasers (or CW-DFB lasers) are able to emit a single wavelength at a time. They can be tuned within a range that can reach up to 10 cm-1; there exists a variety of modulation schemes which can be used for different purposes. Single Mode Lasers are mostly used for spectroscopy. To be operated in continuous-wave (CW).

| Specifications for CW-SM-Q-2209-15-1-HHL-L      |                           |
|---|---------------------------|
| Laser type                                      | QCL quantum-cascade laser |
| Laser Far-field                                 | ТМ00                      |
| Operating mode                                  | CW continuous wave        |
| Emission type                                   | SM singlemode             |
| Target frequency [cm <sup>-1</sup> ]            | 2209.0 ± 0.0              |
| Avg optical power [mW]                          | 15.0                      |
| Full Tuning [cm <sup>-1</sup> ]                 | 1.0                       |
| Temperature Reachable Range [cm <sup>-1</sup> ] | 3.0                       |
| Is Centered                                     | No                        |
| Package Interface                               | HHL-L                     |
| Heatsink temperature max [°C]                   | 20                        |
| Minimum Voltage [V]                             | 7.0                       |
| Maximum Voltage [V]                             | 14.0                      |
| Minimum Current [mA]                            | 50.0                      |
| Maximum Current [A]                             | 1.2                       |
| Fabrication time [days]                         | 56                        |

| Definitions                                     |   |
|---|---|
| Laser far-field                                 | Spatial mode of the laser in the far field.   |
| Operating mode                                  | Operating mode of the driver electronics.   |
| Emission type                                   | Spectral behavior of the laser.   |
| Target frequency [cm <sup>-1</sup> ]            | Target single-mode emission frequency.  |
| Avg optical power [mW]                          | Average optical power at target emission frequency.   |
| Full Tuning [cm <sup>-1</sup> ]                 | Emission tuning range accessible by changing the current while keeping the temperature fixed.         |
| Temperature Reachable Range [cm <sup>-1</sup> ] | Emission tuning range from threshold at lowest temperature to maximum current at maximum temperature. |
| Package interface                               | Laser packaging: either on ceramic submount, or on copper submount, or in specific housing.           |
| Heatsink temperature [°C]                       | Maximum temperature of the heatsink on which the package will be fixed.                               |
| Minimum Voltage                                 | Low end of the potential range for the operation voltage  |
| Maximum Voltage                                 | High end of the potential range for the operation voltage   |
| Minimum Current                                 | Low end of the potential range for the operation current  |
| Maximum Current                                 | High end of the potential range for the operation current   |